

Power Stacker

MODLE		CL1032	CL1232	CL1534	CL1534A
Capacity (Q)	kg	1000	1200	1500	1500
Lifting Height (h3)	mm	3200	3200	3400	3400
Free lift height (h2)	mm	230	230		1190
Min. Fork height	mm	86	86	86	86
Load centre (c)	mm	600	600	600	600
Fork width (b5)	mm	570/695	570/695	570/695	570/695
Fork length (L)	mm	1150	1150	1150	1150
Steering angle	deg	180	180	180	180
Travelling speed	km/h	Without load 5.4, with full load 4			
Lifting speed	mm/s	Without load 128, with full load 91			
Lowering speed	mm/s	Without load 84, with full load 128			
Travelling motor	kw	1.2	1.2	1.2	1.2
Lifting motor	kw	2.2	2.2	3.0	3.0
Battery	ah/v	210/24	210/24	210/24	210/24
Weight of battery	kg	210	210	210	210
Load roller	mm	φ80x70 (tandem) f80x93 (single)			
Support wheel	mm	φ150x54	φ150x54	φ150x54	φ150x54
Driving wheel	mm	φ250x78	φ250x78	φ250x78	φ250x78
Gradient (with/without load)		6/18%	6/18%	6/18%	6/18%
Brake		Electromagnetic			
Speed controlling		Electronic / stepless			
Transmission		Gear			
Weight	kg	670	690	740	860
Dimension	Y	mm	1160	1160	1168
Dimension	L1	mm	1860	1860	1925
Dimension	H1	mm	2095	2095	1695
Dimension	H4	mm	3530	3530	3904
Dimension	E	mm	180	180	180
Dimension	B1	mm	805	805	805
Dimension	Wa	mm	1460	1460	1465

